

# Digital Migration Radio PD405

Digital voice, louder and clearer  
Analogue & Digital Mixed Channel



## Features

Private call, Group call and All call

Small, Sleek, Light

In digital mode, the radio operates up to 16 hours under a duty cycle of 5-5-90 @1500mAh.

IP55 & MIL-STD-810 C/D/E/F/G standards

Pre-programmed Text Message

Support one touch pre-programmed text messages and voice calls.

Dual Mode (Analogue & Digital) ensures a smooth migration from analogue to digital.

DMRA Direct Mode TDMA (True 2-slot) supports two voice calls simultaneously.

Voice-operated Transmit (VOX) allows you to trigger the voice transmission by voice directly.

Analogue & Digital Mixed Channel supports automatically detecting signal type and switching between analogue and digital mode.



## Highlights

- Digital Voice, Louder and Clearer
- Double Channel Capacity
- Analogue & Digital Mixed Channel
- Easy Operation
- Durable, IP55 & MIL-STD-810 C/D/E/F/G standards
- Affordable



## Target Markets



### Construction

At the noisy construction site, a radio with good voice quality and reliable in use can make all the difference.



### Security

Steady wireless signal receiving improves security work performance and reduces loss.



### Warehouse

A durable battery supports full shifts without recharge.



### Factory

Military standard and good dust-proof & water-proof rating (IP55) protect the radio from damage in complex environment of factory.

## Standard



Li-ion battery  
(1500mAh)  
BL1504



Belt clip  
BC08



General MCU Rapid-rate Charger  
(for Li-Ion/Ni-MH batteries)  
CH10A07



Short antenna



Switching Power Adapter



Hand strap

## Options



# Specifications

General	
Frequency Range	UHF: 400-470MHz, VHF: 136-174MHz
Channel Capacity	32
Zone Capacity	3
Channel Spacing	25/12.5KHz
Operating Voltage	7.4V
Battery	1500mAh (Li-Ion) 2000mAh (Li-Ion)
Battery Life (5/5/90)	Analog/Digital: 12/16 hours (1500mAh) 16/22 hours (2000mAh)
Weight	270g
Dimensions	112x54x28mm
Frequency Stability	±0.5ppm
Antenna Impedance	50Ω
Receiver	
Sensitivity (Digital)	0.22μV / BER 5%
Sensitivity (Analog)	0.22μV (Typical) (12dB SIN AD) 0.4μV (20dB SIN AD) 0.22μV (12dB SIN AD)
Adjacent Selectivity	TIA-603 60dB @ 12.5KHz/70dB @ 25KHz
	ETSI 60dB @ 12.5KHz/70dB @ 25KHz
Spurious Response Rejection	TIA-603 70dB @ 12.5/25KHz
	ETSI 70dB @ 12.5/25KHz
Inter-modulation	TIA-603 70dB @ 12.5/25KHz
	ETSI 65dB @ 12.5/25KHz
Hum & Noise	40dB @ 12.5KHz 45dB @ 25KHz
Rated Audio Power Output	0.5W
Rated Audio Distortion	≤3%
Audio Response	+1 ~ -3dB
Conducted Spurious Emission	<-57dBm

Transmitter	
RF Power Output	VHF High power: 5W VHF Low power: 1W UHF High power: 4W UHF Low power: 1W
FM Modulation	11K0F3E @ 12.5KHz 16K0F3E @ 25KHz
4FSK Digital Modulation	12.5KHz Data Only: 7K60FXD 12.5KHz Data & Voice: 7K60FXW
Conducted/Radiated Emission	-36dBm <1GHz, -30dBm >1GHz
Modulation Limiting	±2.5KHz @ 12.5KHz ±5.0KHz @ 25KHz
FM Hum & Noise	40dB @ 12.5KHz 45dB @ 25KHz
Adjacent Channel Power	60dB @ 12.5KHz, 70dB @ 25KHz
Audio Response	+1 ~ -3dB
Audio Distortion	≤3%
Digital Vocoder Type	AMBE++
Digital Protocol	ETSI-TS102 361-1,-2,-3
Environmental	
Operating Temperature	-30°C~ +60°C
Storage Temperature	-40°C~ +85°C
ESD	IEC 61000-4-2 (Level 4) ±8kV (Contact) ±15kV (Air)
Dustproof & Waterproof	Ip55 Standard
Humidity	Per MIL-STD-810 C/D/E/F/G Standard
Shock & Vibration	Per MIL-STD-810 C/D/E/F/G Standard

PD40X, X=0, 2, 5, 6 or 8, model number varies geographically. For details, please contact our regional sales representatives.

All specifications are subject to change without notice due to continuous development.



## Hytera Communications Corporation Limited

**Address:** Hytera Tower, Hi-Tech Industrial Park North, Beihuan Rd., Nanshan District, Shenzhen, China

**Tel:** +86-755-2697 2999 **Fax:** +86-755-8613 7139 **Post:** 518057

**Http://www.hytera.com** **Stock Code:** 002583.SZ



Hytera retains right to change the product design and specification. Should any printing mistake occur, Hytera doesn't bear relevant responsibility. Little difference between real product and product indicated by printing materials will occur by printing reason.

**HYT, Hytera** are registered trademarks of Hytera Communications Co., Ltd.

© 2013 Hytera Communications Co., Ltd. All Rights Reserved.