

Digital Migration Radio PD6 Series

DMR Standard Radio, Feature-Rich, Innovative Design,
Compact Size, Integrates with Hytera Applications



Features

Small, Sleek, Light

The size is 119 X 54 X 27mm (PD60X)/122 X 54 X 27mm(PD66X/68X), PC & Metal frame, weight is 290g (PD60X)/310g (PD66X/68X).



IP67 Compliance

IP67 rated withstanding up to 1m submersion for 30 minutes or more.




Rugged & Reliable

Compliant with MIL-STD-810 C/D/E/F/G standards.

Pseudo Trunk

This virtual trunking feature allocates a free timeslot for urgent communications. This effectively enhances frequency efficiency and allows you to communicate in a timely manner in emergency situations.



Solt 1, Solt 2 are automatically assigned to voice call 1 or voice call 2.

Full Band

Expanded frequency range of 400-527MHz.

Dual Mode (Analog & Digital)

Dual mode (analog & digital) operation ensures a smooth analog to digital migration.

Secure Communication

Provides basic/advanced digital encryption and Scrambler feature in analog mode.

Advanced Signaling

Supports multiple advanced analog signaling modes, including HDC1200, 2-Tone and 5-Tone, providing better integration into existing analog radio fleets.

DMRA Data Service

The data protocol is fully compliant to DMRA standard.

GPS Positioning (Factory Option)

The built-in GPS module supports GIS applications.

Man Down (Factory Option)

When a user falls down, the radio can automatically alert others.

Further Development Port

The reserved side port in PD60X allows users or any third party partner to further develop other helpful applications to extend radio functionalities.

One Touch Call/Text

Supports One Touch features that comprise of Preprogrammed Text Messages, Voice Calls and Supplementary Features. PD68X supports input 256 character message via keyboard.

Supplementary Features


PD60X provides radio enable/disable, remoter monitor and Priority Interrupt.

Radio Priority-Based Interruption

Enable an administration or manager radio to interrupt calls for emergency or urgent communication.

DMO True 2-Slot

In DMO Hytera can provide 2-slot communication, which allows for 2 talk paths on 1 frequency.



Solt 1 used for voice call , Solt 2 used for voice call 2

Small, Sleek, Light

The size is 119 X 54 X 27mm (PD60X)
122 X 54 X 27mm (PD66X/68X),
weight is 290g (PD60X)/310g (PD66X/68X).

Metal Frame

Metal frame design,
smooth texture,
comfortable to hold and use.



Target Markets



Construction

At the noisy construction site a good voice quality radio can make all the difference.



Forestry

Safety functions (man down, lone worker, emergency alarm) give you peace of mind when working alone or on remote locations.



Bank

Complete dispatch system can provide security recording and monitoring.




Factory

Highest dust and water rating (IP67) to withstand dust and liquid impact on the factory floor.

Applications

This is a sample topology of Hytera dispatch system: server, clients, gateway (repeater), subscribers (portables, mobiles).

Hytera dispatch system provides a variety of dispatching features: such as selective voice calls, voice recording, GPS tracking, alarm management, and much more.



Accessories



Pictures above are for reference only and may vary from actual products.

| | | | |
|-----------------|--|----------------|---|
| BL1502 | Li-ion Battery (1500mAh) | EHN21 | Remote C-Earset |
| BL2010 | Li-ion Battery (2000mAh) | ESN14 | Remote Earbud |
| RO03 | Strap | EHN20 | Remote Swivel Earset |
| MCA08 | MCU Multi-Unit Charger (for Thick Battery) | EAN22 | Detachable Earpiece with Transparent Acoustic Tube |
| MCA05 | Battery Optimizing System | PC45 | Programming Cable (USB Port) |
| BC19 | Belt Clip | NCN011 | Nylon Carrying Case (half-folded, non-swivel, black) |
| ESW01-N2 | Wireless Earset Kit | CH10A07 | General MCU Rapid-rate Charger (for Li-Ion/Ni-MH Batteries) |
| Antenna | | Adapter | |

High-Capacity Battery & Battery Charger:

BL1502 Li-ion Battery 1500mAh; BL2010 Li-ion Battery 2000mAh, MCA05 Battery Optimizing System & MCA08 MCU Multi-Unit Charger (for Thick Battery) . For users requiring long-time operation, a high-capacity battery with battery optimizing system is undoubtedly the best match. The 2000mAh Li-ion battery for PD60X ensures up to 16 hours of work.

Audio Accessories:

EHN21 Remote C-Earset, ESN14 Remote Earbud, EHN20 2-wire Surveillance Earpiece with Transparent Acoustic Tube (Black), EAN22 Detachable Earpiece with Transparent Acoustic Tube. PD60X has a variety of audio accessories for flexible use in different environments.

Specifications

| General | |
|-----------------------------|---|
| Frequency Range | VHF: 136-174MHz UHF1: 400-527MHz |
| Channel Capacity | 1024 |
| Zone Capacity | 3 (PD60X)/64 (PD66X/68X) |
| Channel Spacing | 25/20/12.5KHz |
| Operating Voltage | 7.4V |
| Battery(Li-Ion) | 1500mAh/2000mAh |
| Battery Life (5/5/90) | Analog: about 11 Hours Digital: about 16 Hours |
| Weight | 290g (PD60X)/310g (PD66X/68X) |
| Dimensions | 119 X 54 X 27mm (PD60X) 122 X 54 X 27mm (PD66X/68X) |
| Frequency Stability | ±0.5 ppm |
| Antenna Impedance | 50Ω |
| Receiver | |
| Sensitivity (Analog) | 0.22μV (12dB SIN AD) 0.22μV (Typical) (12dB SIN AD) 0.4μV (20dB SIN AD) |
| Sensitivity (Digital) | 0.22μV/BER 5% |
| Adjacent Selectivity | TIA-603 60dB @ 12.5KHz/70dB @ 20 & 25KHz |
| | ETSI 60dB @ 12.5KHz/70dB @ 20 & 25KHz |
| Spurious Response Rejection | TIA-603 70dB @ 12.5/20/25KHz |
| | ETSI 70dB @ 12.5/20/25KHz |
| Inter-Modulation | TIA-603 70dB @ 12.5/20/25KHz |
| | ETSI 65dB @ 12.5/20/25KHz |
| Hum & Noise | 40dB @ 12.5KHz 43dB @ 20KHz 45dB @ 25KHz |
| Rated Audio Power Output | 0.5W |
| Rated Audio Distortion | ≤3% |
| Audio Response | +1 ~ -3dB |
| Conducted Spurious Emission | <-57dBm |

PD60X/66X/68X, X=0, 2, 5, 6 or 8, model number varies geographically. For details, please contact our regional sales representatives.

| Transmitter | |
|-------------------------------------|--|
| RF Power Output | VHF High power 5W VHF Low power 1W UHF High power 4W UHF Low power 1W |
| FM Modulation | 11K0F3E @ 12.5KHz 14K0F3E @ 20KHz 16K0F3E @ 25KHz |
| 4FSK Digital Modulation | 12.5KHz Data Only: 7K60FXD 12.5KHz Data & Voice: 7K60FXW |
| Conducted/Radiated Emission | -36dBm <1GHz -30dBm >1GHz |
| Modulation Limiting | ±2.5KHz @ 12.5KHz ±4.0KHz @ 20KHz ±5.0KHz @ 25KHz |
| FM Hum & Noise | 40dB @ 12.5KHz 43dB @ 20KHz 45dB @ 25KHz |
| Adjacent Channel Power | 60dB @ 12.5KHz 70dB @ 20/25KHz |
| Audio Response | +1 ~ -3dB |
| Audio Distortion | ≤3% |
| Digital Vocoder Type | AMBE++ or SELP |
| Digital Protocol | ETSI-TS102 361-1,-2,-3 |
| Environmental | |
| Operating Temperature | -30°C ~ +60°C |
| Storage Temperature | -40°C ~ +85°C |
| ESD | IEC 61000-4-2 (Level 4) ±8kV (Contact) ±15kV (Air) |
| American Military Standard | MIL-STD-810 C/D/E/F/G |
| Dustproof & Waterproof | IP67 Standard |
| Humidity | Per MIL-STD-810 C/D/E/F/G Standard |
| Shock & Vibration | Per MIL-STD-810 C/D/E/F/G Standard |
| GPS | |
| TTFF (Time To First Fix) Cold Start | <1 minute |
| TTFF (Time To First Fix) Hot Start | <10 seconds |
| Horizontal Accuracy | <10 meters |

All specifications are subject to change without notice due to continuous development.



Hytera Communications Corporation Limited

Address: Hytera Tower, Hi-Tech Industrial Park North, Beihuan Rd.,
Nanshan District, Shenzhen, China

Tel: +86-755-2697 2999 Fax: +86-755-8613 7139 Post: 518057

Http://www.hytera.com Stock Code: 002583.SZ



Hytera retains right to change the product design and specification. Should any printing mistake occur, Hytera doesn't bear relevant responsibility. Little difference between real product and product indicated by printing materials will occur by printing reason.

HYT, Hytera are registered trademarks of Hytera Communications Co., Ltd.

© 2013 Hytera Communications Co., Ltd. All Rights Reserved.